

PR SERIES ANALYTICAL – PR224M – 30524385

SPECIFICATIONS

Maximum Capacity	220 g
Readability	0.1 mg
Readability (Certified)	0.001 g
Pan Size	3.5 in (90 mm)
Internal Calibration	InCal™ - Semi Automatic
Draftshield	Included
Auto Door	Not applicable
Auxiliary Display Model	Available as an Accessory

Battery Life	Not applicable
Built-in Ionizer	No
Communication	RS232
Dimensions	12.5 in x 11.9 in x 7.9 in (317 mm x 303 mm x 201 mm) (LxHxW)
Display	LCD with backlight
In-Use Cover	No
Legal for Trade	OIML
Linearity ±	0.0002 g
Minimum Weight (USP, 0.1%, typical)	200 mg

Net Weight	10 lb (4.5 kg)
Pan Construction	Stainless Steel
Power	AC Adapter (Included)
Repeatability, typical	0.0001 g
Stabilization Time	3 s
Tare Range	To capacity by subtraction
Units of Measurement	Milligram; Gram; Carat
Working Environment	operability guaranteed between 41°F and 104°F; 50°F – 86°F, 80%RH, non-condensing (operability guaranteed between 40°C; 10°C – 30°C, 80%RH, non-condensing)
